



BHE2243
7/8" SDS Rotary Hammer

NEW

Model #	BHE2243
Order #	604480420
Single blow energy (measured in joules)	2.3
Variospeed (V) electronics	●
Long lasting motor	●
Suitable for light chiselling work	● (use w/631409000)
Percussion stop for drilling only operations	●
Aluminum die-cast gear housing	●
Reversing switch	●
Metabo slip clutch	●
Rubber coated handle	●
Auto-stop carbon brushes	●
Winding protection grid	●
Maximum Tightening Torque	124 inch lbs.
Capacity	
- in concrete using solid bits	7/8"
- in mild steel	1/2"
- in softwood	1 3/16"
No-load speed (RPM)	0-1150
No-load blows per minute (BPM)	0-5400
Amps	6.0
Rated input watts	800
Tool weight	7.2 lbs.
Shipping weight	11.6 lbs.
Length	13"
Carrying case	344454110 (standard)
Standard Equipment:	Side handle (314000840) Depth gauge (341511630)
Optional Equipment:	Dust extraction kit (631600000)

(See page 29 for SDS-Plus masonry bits)



UHE2650 Multi
1 1/8" Multi-purpose Hammer
w/Rotostop



KHE32
1 1/4" SDS Rotary Hammer
w/Rotostop

NEW

UHE2650 Multi Hammer

3 Tools in 1

1- 2 Speed Drill

2- 1-1/8" Rotary Hammer

3- Chipping Gun

...all in a single unit!

This versatile, powerful rotary hammer lets you perform drilling, impact drilling or rotation-only operations with a single tool.

Unique to this tool is a rotary hammer function that allows for effective drilling of concrete, brick, and other masonry materials. A chiseling function allows chiseling of the same materials. By switching to the two speed drill mode you can effectively drill into virtually any non-masonry material: wood, steel, plastic, glass, etc. All materials, one tool!

To further enhance versatility and functionality, the UHE Multi Hammer is furnished with a quick-change SDS chuck...and an additional quick-change three-jawed chuck that accepts a full range of non-masonry bits and allows bit changes without the use of tools.

SDS chuck



Quick-change, three-jawed chuck



When you're looking for on-the-job versatility and long-lasting performance, the Metabo UHE2650 Multi Hammer gives you more... much more!

Model # Order #	UHE2650 Multi 600952420	KHE32 600232420
Single blow energy (measured in joules)	0-2.75	0-3.5
Vario tacho constamatic (VTC) electronics	●	●
Long lasting motor	●	●
2-speed gear-box for drilling wood or metal	●	
Quick-change chuck system	●	●
Chisel positions	● 30 settings	● 15 settings
Percussion stop for drilling only operations	●	●
Rotation stop for chiseling operations	●	●
Aluminum die-cast gear housing	●	●
Reversing switch	●	●
Metabo slip clutch	●	●
Rubber coated handle	●	●
Carbon brush wear indicator	●	●
Auto-stop carbon brushes	●	●
Winding protection grid	●	●
Electronic speed stabilization	●	●
Variable speed controlled by adjusting dial	●	
Winding temperature monitor	●	
Swivel cord connection	●	
Maximum Tightening Torque	195 inch lbs.	221 inch lbs.

Capacity		
- in concrete using solid bits	1 1/8"	1 1/4"
- in brickwork using thin wall core bits	3 1/8"	n/a
- in mild steel	1/2" - 5/16"	5/8
- in softwood	2 5/8" - 3/4"	1 9/16"
No-load speed (RPM)	0-950/0-2600	0-780
No-load blows per minute (BPM)	0-4400	0-3800
Amps	9.0	7.5
Rated input watts	1010	900
Tool weight	8.1 lbs.	10.5 lbs.
Shipping weight	13.5 lbs.	15.9 lbs.
Length	15 9/16"	15"
Carrying case	344454110 (standard)	344452350 (standard)
Standard Equipment:	Side handle- (314001230) Depth gauge- (343398230) 1/2" Keyless 3-jaw chuck-(301002190) SDS chuck-(316046990)	Side handle- (314000770) Depth gauge- (341511630) SDS chuck (631922000)
Optional Equipment:	Dust extraction kit- (631600000)	Dust extraction kit- (631600000)